



Vredo Overseeders

DZ Agri



Renovate your grass and save money

The Vredo Agri series has an excellent reputation in the worldwide agricultural sector. Every contractor should have the robust, but very precise machine ready to use in the spring, after the first cut or in the autumn, to provide the pastures with lush grass. Renew bare patches, strengthen paths, prevent erosion, repair wildlife damage and sow additional clover, restricting the grow of weeds - these are the reasons to use a Vredo. The Agri series has a standard row distance of 7.5 cm. This is perfect to provide the meadow with a closed grass yield, without waste. The grass seed is placed for optimal germination, because it is enclosed in the fertile soil and protected from birds and drought. Overseeding can be done in one pass and saves up to 80% time and fuel, compared to renovation through ploughing, cultivating, levelling, sowing and rolling.

Plot stays in use

The great advantage of overseeding is that the plot can stay operational. The machine has hard-wearing discs and all the elements are individually suspended. That way, the seed

always gets deposited at the correct depth in the ground and the discs are protected. Optionally, the Agri Serie is available with a packing roller. This roller, with movable cast iron rings, undulates on rough terrain, meaning plots with stones or ditches can be worked.

Unique features

The seed dosage of the Vredo Agri is adjustable, so there is never too much or too little seed being dispersed. You determine the amount of seed, with the help of the practical designed spindle and seed chart, which is equipped with the most common types of grass and mixtures. The seed gets regulated precisely, through the cam wheel and the bottom flap, from the beginning until the end of all its movements. Since the soil conditions and environmental factors like wind and sun are unique, every surface requires its own specific adjustment. With the Vredo Agri this is child's play. By using the calibration tray and the extensive seed chart the dosing is exact and very easily adjustable. This robust machine has been built using high quality materials, which makes it an investment for life.



VREDO double disc principal

Vredo Agri; "when you choose speed and results"

The best in the field



Standard new features



Spindle

To adjust the quantity of seed released by the machine. With use of the seed chart at the inner side of the lid, this is an easy job.



Gas cylinder

To open and close the lid smoothly after filling the seed tank.



LED lights

Bright light with clear signs of direction and brakes for transport on the road.

Options

1



Scraper for packer ring roller

Ingenuously clever scraper to keep every movable packer ring individually clean for an optimal performance, even under wet and heavy conditions.

2



Platform

Strongly recommended when packer ring has been chosen. Stable metal standing platform for filling of the machine.

3



Hill plates

Demountable plates to improve the seed dosage while driving on steep slopes.

4



Stone protection

To avoid getting stones, clods and crop residues in between the discs.

5



Second hectare counter

Ideal for machines that will be rented out. Registers the number of hectares precisely, without the user being able to influence it.

Specifications **Vredo DZ Agri-series**

Seed distribution	Disc diameter	Element	Turf guard	Compaction Roller	Calibrate
Variable 3 till 190 kg/a	Ø 406 mm	Progressive suspension suspension length 0-20mm sowing depth	Adjustable	Refillable, height adjustable 250/290 liter	Calibrate chart, Calibrating trays

Type	Roller	Working width (m)	Transport width (m)	Row distance (cm)	Contents seed hopper	Contents roller	Weight (kg)	Mounting	Required Tractor Power	Dimensions (m)
DZ 225.075	Smooth	2,47	2,69	7,5	250 l.	250 l.	1240	3-point	80 hp	1.31x2.69x1.23
DZ 225.075	Packer	2,47	2,69	7,5	250 l.	250 l.	1970	3-point	90 hp	1.31x2.69x1.23
DZ 229.075	Smooth	2,85	3,00	7,5	290 l.	290 l.	1410	3-point	90 hp	1.31x3.00x1.23
DZ 229.075	Packer	2,85	3,00	7,5	290 l.	290 l.	2205	3-point	100 hp	1.31x3.00x1.23

www.vredo.com
+31 (0) 488 411 254
sales@vredo.com

Copyright © 2016 Vredo Dodewaard BV. All rights reserved.
All product information was correct at time of printing.

Dealer:

Vredo

The best in the field